

REPORT

7S Series



finder®

SWITCH TO THE FUTURE



Relay modules
with forcibly
guided contacts
for safety
applications
up to SIL 3


Type 7S.43 and 7S.63

Features

- 3 pole: 2 NO + 1 NC, 6A
- Auxiliary contact: 1 NO 6 A
- Double channel architecture (1oo2)
- Contact material AgSnO₂ & AgNi+Au
- Screw and Screwless terminal version available
- 22.5 mm wide
- 35 mm rail (EN 60715) mounting

- Safety expansion module with class A forcibly guided contact relays EN 61810-3 (previously EN 50205) for safety application up to SIL 3
- SIL 3 evaluated according to EN 61508, for use in functional safety application according to EN 62061 up to SIL 3 and according to IEC 13849-1 up to PL e
- Coils from 24 to 110 V DC with operating range (0.85...1.1)UN
- LED indication of coil status


Screwless terminals



Type 7S.43.x.xxx.0211

- 3 pole (2 NO + 1 NC)
- Double channel architecture (1oo2)
- Rated current 6 A
- Nominal coil voltage: 12 - 24 - 48 - 110 V DC
- Cadmium free contacts
- Contact material AgSnO₂ & AgNi+Au


Screw terminals



Type 7S.63.x.xxx.0211

- 3 pole (2 NO + 1 NC)
- Double channel architecture (1oo2)
- Rated current 6 A
- Nominal coil voltage: 12 - 24 - 48 - 110 V DC
- Cadmium free contacts
- Contact material AgSnO₂ & AgNi+Au

Contact diagram



11		33	23
	47	48	
A1	A1	A2	A2
12		34	24